

## MTPX-EH ELEGANT EH PROXIMITY READER

MTPX-EH is a proximity reader with a polycarbonate front plate, available in a silver metal housing or in black ABS. It is elegant, slim and compact and its design is suitable for inside and outside use. MTPX-EH is compatible with most access controllers and Time and Attendance systems. It incorporates access control standard protocols such as Wiegand 24 to 42 bit.



- Surface mount
- Housing: moulded aluminium/ABS
- Indoor/outdoor use
- Proximity reader compatible EM 4002/4100 and HID (125 kHz)
- Configurable WIEGAND output 24, 26, 32, 34, 35, 37, 40, 42bit.
- Green and Red Led: externally controlled
- Reading distance: up to 5 cm
- Audible and visual feedback
- Configurable sound mode (Buzzer ON/OFF)
- Configurable idle backlight (ON/OFF)
- Tamper protection: when opened or dismantled
- Operates on 9 to 14V DC
- Current Consumption: max 50 mA
- IP 65
- Operating temperature: -20°C to +50°C









MTPXS-EH Silver - Metal MTPXBK-EH Black - ABS












Orange LED Idle Mode Red LEDGreen LEDAccess DeniedAccess Granted

DIMENSIONS

LINGION



92 mm

25 mm metal; 27 mm ABS