

Personal attack buttons

Instruction manual

HB 205 / HB 205-L



DESCRIPTION

HB 205 Series Personal attack buttons are mechanical buttons aimed for banks, gas stations, warehouses, governmental institutions or other places where you can expect a threat.

HB 205 is available in two variants:

HB 205 with momentary NC/NO function. It has an antitamper switch to protect against unauthorized opening.


HB 205-L with NC function and latching push-button. The button is reset to its initial state after a further button push. There is also an input to control the built-in LED and an anti-tamper switch to protect against unauthorised opening.

INSTALLATION

Panic buttons of MC 205 Series have 7 screw terminals. Connection as below:




HB 205



- 1 Spare
- 2 NO
- 3 NC
- 4 C
- 5 Spare
- 6 Tamper
- 7 Tamper

HB 205-L



- 1 Supply Voltage for LED (-)
- 2 Supply Voltage for LED (+)
- 3 C
- 4 NC
- 5 Spare
- 6 Tamper
- 7 Tamper

TECHNICAL DATA

NC/NO Alarm output HB 205: Alarm output HB 205-L: 30 VDC / 100 mA Contact data: Yes, 12 VDC / 50 mA Sabotage contact: Supply voltage (for LED of HB 205-L): 9 - 30 VDC with resistance in series (1Kohm) LED (HB 205-L): Working temperature: -10 - +55°C Housing protection class: IP 31 62 x 50 x 35 Dimensions (L x W x H):

Compliance: