Casings for recorders - universal





DESTINATION

The enclosure construction is compliant with the requirements of the General Data Protection Regulation (GDPR), as personal data must be protected and stored securely.

The enclosure protects the recorder against unauthorized access or theft (two keys included). Made of 1 mm steel plate. The set includes two keys (different code) for each lock and a tamper switch indicating enclosure opening or unwanted removal of the enclosure from the wall.

Due to the vertical installation and low depth, it is ideal for places where deeper enclosures or cabinets type Rack19" cannot be installed. After opening the enclosure, the front cover is held in a horizontal position, providing easy access to the buttons on the front panel of DVR.

The enclosure has a special holder with retaining straps that allows for the installation of recorders of the following dimensions: width from 375 mm, height: from 95 mm, depth: from 335mm.

W=435, H=500, D + D ₂ =121+14 [mm, +/-2]
W ₁ =375, H ₁ =335, D ₁ =95 [mm, +/-2]
8,20kg / 8,90kg [+/-0,1kg]
class II, -10°C÷ 40°C
sheet steel DC01, thickness: 1,0mm, corrosion protection, color: RAL 9005 (black matt)
indoor
2 x microswitch: opening and detachment of the enclosure,
0,5A@50V/DC max. NC- normally closed contacts
Lock MR008 (different code) x 2 pcs
distance from the wall 14mm
The set includes two keys (different code) for each lock
RoHS, 2 year from the production date