

TECHNICAL DATA SHEET



Secury360 Box V3 + LTE

You don't build a castle on sand. You need a strong foundation. That's why the S360 box contains the best hardware, which can also run your VMS all at once. So you don't need an extra PC in your setup!



Technical data	WITHOUT HD		WITH 2,5" HD	WITH 3,5" HD
Dimensions	217mm x 75mm x 247mm			
Weight	1,90 kg	2,22 kg	2,48 kg	
I/O Inputs				
Number	6			
Type	15VDC, galvanic isolated, to be used with a voltage-free contact			
Connector type	2 x 4 pole plugable connector. Common ground.			
Wire range	1.5mm2 / stranded or solid			
Wire strip length	6 - 7mm			
I/O Outputs				
Number	6			
Type	Voltage-free relay contact			
Contact type	1A, 220 VDC/250 VAC			
Connector type	4 x 6 pole plugable connector			
Wire range	1.5mm2 / stranded or solid			
Wire strip length	6 - 7mm			
Power supply				
Input voltage	12V ... 24V			
Maximum input current	1.0A	1.3A	2.1 A (3)	
Maximum input power	12W	15.6W	25.2W	
General				
EMC immunity/emission	EN50130-4			
Storage temperature	-40°C ... +85°C			
Operation temperature	-20°C ... 65°C	-20°C ... 65°C	-20°C ... 55°C (1)	
Relative humidity	95%, no condensation			
Protection rating	IP30			
Assembly	No addition	2.5" assembly kit	3.5" assembly kit	
LTE				
Brand	SIMCom SIM7600SA-H-PCIE			
Data transfer	LTE: 150 Mbps DL - 50 Mbps UL			
	HSPA+: 42 Mbps DL - 5,76 Mbps UL			
	WCDMA: 384 Kbps DL - 384 Kbps UL			
	GPRS/EDGE: 236,8 Kbps DL - 236,8 Kbps UL			
Protocol	TCP/IP/IPV4/IPV6/Multi-PDP/FTP/FTPS/HTTP/HTTPS/DNS			

(1) Only guaranteed with the use of the fan extension module

(2) Weight without HD mounted

(3) With 3.5" WD8001PURP HD