TELETEK

NEW - Ceiling mount sounder with built-in standard base

SensoIRIS CSOU/CSOU IS

EN 54-3
EN 54-17

SensoIRIS CSOU addressable sounder base provides flexibility. - It can be used for notification as a fire alarm sounder base, to be used with SensoIRIS VAD WST/ RST -visual alarm device EN54-23 certificated and to be mounted with any SensoIRIS detector, which limits the number of installation points within a building, making installation faster and more efficient.

The sounder base is compatible with SensoIRIS series of addressable detectors. When being used for notification only, it can be used with BS cover plate, instead of a detector, providing a discreet, standalone fire alarm sounder.

Base
SensoIRIS B124 / SensoIRIS B124- HP
For easy mounting and cabling

Sounder Part
SensoIRIS CSOU/CSOU IS
Sounder with built-in base
EN54-3 / EN 54-17 certificated

Detector
SensoIRIS Detectors
Addressable detectors T110/ S130/M140
or BS Cover

Features:

- One point of installation for detector and sounder with no additional wiring
- Two sound levels - LOW: 81dB (A) ±3dB@3m; HIGH: 88dB (A) ±3dB@3m
- 32 tone types selectable from the panel
- Up to 100 sounders on loop (on low level sound)
- Loop synchronization for uniform and clear alarm signal
- Protection Degree -IP21C, type A
- Loop powered
- Compatible with SensoIRIS detector series
- Mounts directly on standard B124 or B124-HP to save time
- Optional cover when the base is used only as a sounder

VAD WST/ RST

B124

B124-HP

SensoIRIS Detector

BS Cover