


## DS-2CD2183G2-I(S) 8 MP AcuSense Fixed Dome Network Camera

### AcuSense



Empowered by deep learning algorithms, Hikvision AcuSense technology brings human and vehicle targets classification alarms to front- and back-end devices. The system focuses on human and vehicle targets, vastly improving alarm efficiency and effectiveness.

- High quality imaging with 8 MP resolution
- Clear imaging against strong backlight due to 120 dB true WDR technology
- Efficient H.265+ compression technology
- Focus on human and vehicle targets classification based on deep learning
- -S: Audio and alarm interface available
- Water and dust resistant (IP67) and vandal-resistant (IK10)



## ▪ Specification

| Camera                 |                                                                                                                                                                                        |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor           | 1/2.8" Progressive Scan CMOS                                                                                                                                                           |
| Min. Illumination      | Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR                                                                                                                                  |
| Shutter Speed          | 1/3 s to 1/100,000 s                                                                                                                                                                   |
| Slow Shutter           | Yes                                                                                                                                                                                    |
| P/N                    | P/N                                                                                                                                                                                    |
| Wide Dynamic Range     | 120 dB                                                                                                                                                                                 |
| Day & Night            | IR cut filter                                                                                                                                                                          |
| Angle Adjustment       | Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 355°                                                                                                                                   |
| Lens                   |                                                                                                                                                                                        |
| Lens Type              | Fixed focal length, 2.8 and 4 mm optional                                                                                                                                              |
| Focal Length & FOV     | 2.8 mm, horizontal FOV 107°, vertical FOV 57°, diagonal FOV 128°<br>4 mm, horizontal FOV 87°, vertical FOV 46°, diagonal FOV 105°                                                      |
| Lens Mount             | M12                                                                                                                                                                                    |
| Iris Type              | Fixed                                                                                                                                                                                  |
| Aperture               | F1.6                                                                                                                                                                                   |
| DORI                   |                                                                                                                                                                                        |
| DORI                   | 2.8 mm: D: 88 m, O: 35 m, R: 17 m, I: 9 m<br>4 mm: D: 108 m, O: 43 m, R: 22 m, I: 11 m                                                                                                 |
| Illuminator            |                                                                                                                                                                                        |
| Supplement Light Type  | IR                                                                                                                                                                                     |
| Smart Supplement Light | Yes                                                                                                                                                                                    |
| IR Wavelength          | 850 nm                                                                                                                                                                                 |
| IR Range               | Up to 30 m                                                                                                                                                                             |
| Video                  |                                                                                                                                                                                        |
| Max. Resolution        | 3840 × 2160                                                                                                                                                                            |
| Main Stream            | 50 Hz: 20 fps (3840 × 2160)<br>25 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)<br>60 Hz: 20 fps (3840 × 2160)<br>30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) |
| Sub Stream             | 50 Hz: 25 fps (640 × 480, 640 × 360)<br>60 Hz: 30 fps (640 × 480, 640 × 360)                                                                                                           |
| Third Stream           | 50 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)<br>60 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)<br>*Third stream is supported under certain settings.   |
| Video Compression      | Main stream: H.265/H.264/H.264+/H.265+<br>Sub-stream: H.265/H.264/MJPEG<br>Third stream: H.265/H.264<br>*Third stream is supported under certain settings.                             |
| Video Bit Rate         | 32 Kbps to 16 Mbps                                                                                                                                                                     |
| H.264 Type             | Baseline Profile/Main Profile/High Profile                                                                                                                                             |
| H.265 Type             | Main Profile                                                                                                                                                                           |
| H.264+                 | Main stream supports                                                                                                                                                                   |

|                             |                                                                                                                                                                                                                                        |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| H.265+                      | Main stream supports                                                                                                                                                                                                                   |
| Bit Rate Control            | CBR/VBR                                                                                                                                                                                                                                |
| Scalable Video Coding (SVC) | H.264 and H.265 encoding                                                                                                                                                                                                               |
| Region of Interest (ROI)    | 1 fixed region for main stream and sub-stream                                                                                                                                                                                          |
| <b>Audio</b>                |                                                                                                                                                                                                                                        |
| Audio Compression           | -S: G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC                                                                                                                                                                                |
| Audio Bit Rate              | -S: 64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/16 Kbps to 64 Kbps (AAC)/32 to 192 Kbps (MP2L2)/8 to 320 Kbps (MP3)                                                                                                |
| Audio Sampling Rate         | -S: 8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz                                                                                                                                                                                                |
| Environment Noise Filtering | -S: Yes                                                                                                                                                                                                                                |
| <b>Network</b>              |                                                                                                                                                                                                                                        |
| Protocols                   | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP                                                                                         |
| Simultaneous Live View      | Up to 6 channels                                                                                                                                                                                                                       |
| API                         | Open Network Video Interface (Profile S, Profile G), ISAPI, SDK                                                                                                                                                                        |
| User/Host                   | Up to 32 users. 3 user levels: administrator, operator and user                                                                                                                                                                        |
| Security                    | Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2, WSSE and digest authentication for Open Network Video Interface       |
| Network Storage             | NAS (NFS, SMB/CIFS), auto network replenishment (ANR)                                                                                                                                                                                  |
| Client                      | iVMS-4200, Hik-Connect, Hik-Central                                                                                                                                                                                                    |
| Web Browser                 | Plug-in required live view: IE 10, IE 11<br>Plug-in free live view : Chrome 57.0+, Firefox 52.0+<br>Local service: Chrome 57.0+, Firefox 52.0+                                                                                         |
| <b>Image</b>                |                                                                                                                                                                                                                                        |
| Image Parameters Switch     | Yes                                                                                                                                                                                                                                    |
| Image Settings              | Rotate, mirror, privacy mask, saturation, brightness, contrast, sharpness, gain, white balance adjustable by client software or web browser                                                                                            |
| Day/Night Switch            | Day, Night, Auto, Schedule                                                                                                                                                                                                             |
| Image Enhancement           | BLC, HLC, 3D DNR                                                                                                                                                                                                                       |
| SNR                         | ≥ 52 dB                                                                                                                                                                                                                                |
| <b>Interface</b>            |                                                                                                                                                                                                                                        |
| Ethernet Interface          | 1 RJ45 10 M/100 M self-adaptive Ethernet port                                                                                                                                                                                          |
| On-board Storage            | Built-in memory card slot, support microSD/SDHC/SDXC card, up to 256 GB                                                                                                                                                                |
| Audio                       | -S: 1 input (line in), max. input amplitude: 3.3 Vpp, input impedance:4.7 KΩ, interface type: non-equilibrium; 1 output (line out), max.output amplitude: 3.3 Vpp, output impedance: 100 Ω, interface type: non-equilibrium,mono sound |
| Alarm                       | -S: 1 input, 1 output (max. 12 VDC, 30 mA)                                                                                                                                                                                             |
| Hardware Reset              | Yes                                                                                                                                                                                                                                    |
| <b>Event</b>                |                                                                                                                                                                                                                                        |
| Basic Event                 | Motion detection (human and vehicle targets classification), video tampering alarm, exception                                                                                                                                          |
| Smart Event                 | Line crossing detection, intrusion detection, human and vehicle targets classification                                                                                                                                                 |
| Face Detection              | Yes                                                                                                                                                                                                                                    |

| General                          |                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Linkage Method                   | Upload to FTP/memory card/NAS, notify surveillance center, trigger recording, trigger capture, send email                                                                                                                                                                                                                                               |
| Camera Material                  | Aluminum alloy body<br>Bubble: plastic                                                                                                                                                                                                                                                                                                                  |
| Camera Dimension                 | Ø110.8 mm × 84.7 mm (Ø4.4" × 3.3")                                                                                                                                                                                                                                                                                                                      |
| Package Dimension                | 134 mm × 134 mm × 108 mm (5.3" × 5.3" × 4.3")                                                                                                                                                                                                                                                                                                           |
| Camera Weight                    | Approx. 520 g (1.1 lb.)                                                                                                                                                                                                                                                                                                                                 |
| With Package Weight              | Approx. 720 g (1.6 lb.)                                                                                                                                                                                                                                                                                                                                 |
| Storage Conditions               | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)                                                                                                                                                                                                                                                                               |
| Startup and Operating Conditions | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)                                                                                                                                                                                                                                                                               |
| Web Client Language              | 33 languages<br>English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian |
| General Function                 | Anti-flicker, heartbeat, password reset via email, pixel counter                                                                                                                                                                                                                                                                                        |
| Firmware Version                 | V5.5.113                                                                                                                                                                                                                                                                                                                                                |
| Software Reset                   | Yes                                                                                                                                                                                                                                                                                                                                                     |
| Power Consumption and Current    | 12 VDC, 0.5 A, max. 6 W<br>PoE (802.3af, 36 V to 57 V), 0.25 A to 0.15 A, max. 7.5 W                                                                                                                                                                                                                                                                    |
| Power Supply                     | 12 VDC ± 25%, reverse polarity protection<br>PoE: 802.3af, Class 3                                                                                                                                                                                                                                                                                      |
| Power Interface                  | Ø5.5 mm coaxial power plug                                                                                                                                                                                                                                                                                                                              |
| Approval                         |                                                                                                                                                                                                                                                                                                                                                         |
| EMC                              | FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016); KC (KN 32: 2015, KN 35: 2015)                                                                                                                                  |
| Safety                           | UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013);                                                                                                                                                                                                                                       |
| Environment                      | CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)                                                                                                                                                                                                                                                                           |
| Protection                       | IP67 (IEC 60529-2013), IK10 (IEC 62262: 2002)                                                                                                                                                                                                                                                                                                           |



## ▪ Available Model

DS-2CD2183G2-I (2.8/4 mm)

DS-2CD2183G2-IS (2.8/4 mm)

DS-2CD2183G2-IS (2.8 mm) (Black)


▪ **Dimension**



Unit:mm(inch)

▪ Accessory

▪ Optional

|                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| DS-1271ZJ-110<br>(Black)<br>Pendant Mount                                           | DS-1259ZJ(Black)<br>Junction Box                                                    | DS-1275ZJ-SUS<br>Vertical Pole Mount                                                | DS-1250ZJ<br>Rain Shade                                                               | DS-1272ZJ-110<br>(Black)<br>Wall Mount                                                |
|    |    |    |    |    |
| DS-1280ZJ-DM18<br>Junction box                                                      | DS-1272ZJ-110B<br>(Black)<br>Wall Mount                                             | DS-1276ZJ-SUS<br>Corner mount                                                       | DS-1276ZJ-SUS<br>(Black)<br>Corner Mount                                              | DS-1259ZJ<br>Inclined Ceiling<br>Mount                                                |
|  |  |  |  |  |
| DS-1272ZJ-110B<br>Wall Mount                                                        | DS-1271ZJ-110<br>Pendant Mount                                                      | DS-1272ZJ-110<br>Wall Mount                                                         | DS-1275ZJ-SUS<br>(Black)<br>Vertical Pole Mount                                       | DS-1280ZJ-DM18<br>(Black)<br>Junction Box                                             |
|  |  |  |  |  |
| DS-1250ZJ(Black)<br>Rain Shade                                                      |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
|  |                                                                                     |                                                                                     |                                                                                       |                                                                                       |

Distributed by



## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com