

A red banner with rounded ends is positioned at the top left of the page. It contains the product name in white text.

DS-PDC10DM-EG2-WE
Wireless External DT Detector

- · Slim design for window frame installation
- · IP65 weather resistance for outdoor application
- · Active IR anti-masking
- · Multiple enrollment methods and easy installation
- · Frequency hopping against jamming for reliable transmission











▪ Specification

| | Model | DS-PDC10DM-EG2-WE |
|-----------------------------------|-----------------------------------|---|
| Detection Performance | Detection Method | Passive Infrared,Microwave |
| | Detection Range | Wall Mount: 10m Ceiling Mount: 5m |
| | Detection Angle | 5° |
| | Detection Zones | 32 |
| | Detectable Speed | 0.3~2m/s |
| | Sensitivity | Auto,Pet |
| | White Light Filter | 6500lux |
| | Pet Immunity | Wall Mount: 12Kg Ceiling Mount: None |
| | Microwave Frequency | 24GHz(24.15 to 24.25GHz) |
| | Digital Temperature Compensation | Support |
| | Creep Zone Protection | Support |
| | Anti-masking | Support |
| Feature | Digital Processing | Support |
| | Sealed Optics | Support |
| | Tamper Protection | Front,Rear |
| | Environment Temperature Indicator | Support |
| | Signal Strength Indicator | Support |
| Interface | Power Switch | Power Up Enrolling |
| | LED Indicator | Green(PIR), Red(Microwave), Green+Orange(Mask), Blue(Alarm) |
| Transmission | Transmission Technology | Tri-X Wireless |
| | Transmission Method | Two-Way RF Wireless |
| | Transmission Frequency | 868MHz |
| | Transmission Security | AES-128 Encryption |
| | Transmission Range(Free Space) | 1.6Km |
| | Frequency Hopping | Support |
| | Enrolling Method | Power up,Remote ID,QR Code |
| Electrical Characteristics | Standard Battery Life | 5 years in work status (being triggered 20 times per day) |
| | Power Supply | Battery Powered |
| | Battery Type | CR123A × 2 |
| | Typical Voltage | 3V |
| General | Operation Temperature | -10 °C to 55 °C (14 °F to 131 °F) |
| | Storage Temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| | Operation Humidity | 10% to 90% |
| | IP Rate | IP65 |
| | Dimension(WxHxD) | 29.2mm × 134.4mm × 39.5mm |
| | Weight | 120g |

| | |
|----------------------|---------------------------|
| Mounting Height | 2 to 3.5m |
| Mounting Method | Wall,Ceiling |
| Application Scenario | Indoor,Outdoor |
| Bracket | L-shaped adapter included |

▪ **Installation**



▪ **Available Model**

DS-PDC10DM-EG2-WE

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com