

DS-PDMCX-E-WE

Wireless External Magnet Detector

It is a wireless opening detector that especially for outdoor usage. Robust plastic housing, IP66 weather resistance, UV stable.

- IP66 protective level, UV stable
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission



▪ Specification

| | Model | DS-PDMCX-E-WE |
|-----------------------------------|-----------------------------------|--|
| Detection Performance | Detection Method | Opening Contact |
| | Detection Gap | 76mm Max |
| Feature | Digital Processing | Support |
| | Tamper Protection | Front, Rear |
| | Environment Temperature Indicator | Support |
| | Signal Strength Indicator | Support |
| Interface | Alarm Input | Normally Closed, Normally Open, Impulse Count |
| | Power Switch | Power Up Enrolling |
| | LED Indicator | Blue (Alarm) |
| Transmission | Transmission Technology | Tri-X Wireless |
| | Transmission Method | Two-Way RF Wireless |
| | Transmission Frequency | 868MHz |
| | Transmission Security | AES-128 Encryption |
| | Transmission Range(Free Space) | 1.6Km |
| | Frequency Hopping | Support |
| | Enrolling Method | Power up, Remote ID, QR Code |
| Electrical Characteristics | Standard Battery Life | 5 years |
| | Power Supply | Battery Powered |
| | Battery Type | CR123A x 1 |
| | Typical Voltage | 3V |
| General | Operation Temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| | Storage Temperature | -30 °C to 60 °C (-22 °F to 149 °F) |
| | Operation Humidity | 10% to 90% |
| | Dimension(WxHxD) | Sensor: 40.5 mm × 146 mm × 40.9 mm Magnetic Stick: 30.5 mm × 146 mm × 40.9 mm |
| | Weight | 247 g |
| | Application Scenario | Outdoor, IP66 |

▪ Available Model

DS-PDMCX-E-WE

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com