

# AT2PG34-200

## Back Lit Polycarbonate Access Keypad



### Illuminated Single Door Keypad

#### Description

Back Lit Piezo Keypad, single door access control, 200 user code, front mounted. Dimensions are 3.2" x 4.5" with tamper proof mounting system for single gang box. Rugged Polycarbonate housings are one piece construction with blue back lit graphics with full Braille markings for ADA compliance. Fully weather proof and completely potted. Connection is via cable and 2A Form C relay.

#### Features

- Easily programable through the keypad
- 200 Codes (1 Master, 200 User Codes)
- Tamper Alert
- Triggers CCTV or doorbell or controls an auxiliary device

#### Characteristics

- Illuminated: Fully back lit in blue
- ADA: Fully compliant with Braille
- Field Configurable: Door open time, Remote open
- Proven reliability: Tested for 50,000,000 cycles
- Weatherproof: For use in harshest outdoor conditions
- Touch Activated: Operable with gloves, tools, etc.
- Vandal Resistant: For use in high traffic and abusive areas

## TECHNICAL DATA

#### Electrical Data

Key Function	N.O. Momentary
Voltage	12-16VDC
Relay	2A Form C
Power Consumption	150 mA
Operating Cycles	>50,000,000
Function	Latch Mode
Output	Relay, CCTV or Remote Open
User Codes	200
Shielding	ESD, RFI, EMI Proof
User Feedback	Status LED/Beeper

#### Mechanical Data

Housing Materials	Polycarbonate
Housing Method	One piece construction
Actuating Force	3-5 Newton
Connection	Cable
Actuating Travel	0.002 mm
Shock Protection	IK 06

#### Environmental Data

Operating Temperature	-20 to +75 °C
Storage Temperature	-40 to +125 °C
IP-Protection	IP-68