

Proximity reader 3 to 5 cm local bus output RS-485 (EM & HID)



Codification and designation :

DA-4020 : Proximity reader 3 to 5 cm local bus output RS-485 (EM & HID)

General description :

Elegant and compact 125 kHz reader. The housing, in black ABS, comes with a big rectangular LED. Designed to be installed either outside or inside, it has a RS-485 local bus. Its tricolor LED, tamper and buzzer are managed directly by the door controller. It can read Mifare Classic, Desfire and Ultralight.

Technical characteristics :


- Mounting: Surface
- Housing: ABS
- Colours: Black
- Resin potted electronics: Yes
- Technology: Proximity
- Reading type: EM 4002/4100 and HID (125 kHz)
- Read range: Up to 5 cm
- Operating frequency: 125 kHz
- Output: RS-485
- Visible signal: controlled by the host
 - Green LED: Access Granted
 - Red LED: Access Denied
 - Orange LED: Sleep Mode
- Audible signal: 1 internal buzzer - managed by the host
- Tamper: Yes - managed by the host
- Voltage: 9-14 V DC
- Consumption: Max. 130 mA

MECHANICAL CHARACTERISTICS

- IP rating: IP65
- Dimensions (L x H x W): 51 x 92 x 27 mm
- Weight: ~0.15 kg
- Operating temperature: -20°C to +50°C
- Operating humidity: 0 to 95% (non-condensing)


Proximity reader 3 to 5 cm local bus output RS-485 (Mifare-Desfire)

Mechanical dimensions and weight :



Material : ABS
Weight : ~0,15 kg

Wiring :



Other versions : No other version

Package : Delivered with wiring plan



Rue de la Gare,30
B-1420 Braine-l'Alleud
Belgium
Tel : +32 (0)2 389 16 40
Fax : +32 (0)2 387 14 02
contact@dinec.be
www.dinec.be

Your distributor :

