DUCT Detector

Smoke detector housing



- Detects and limit the spread of smoke inside the building HVAC ducts
- Compatible with SensolRIS B124 and SensoMAG B24 bases
- Sampling and outlet pipes included (27 cm)

Duct Detector housing is a special box that works in combination with standard smoke detectors. The design allows the air from the duct to pass through the device, while analyzing it for the presence of smoke particles. The DUCT detector includes 2 pipes – sampling pipe and outlet pipe, as each of them is 27 cm long.

The housing is compatible with SensoIRIS B124 and SensoMAG B24 bases for connecting SensoIRIS S130 and SensoMAG S30 respectively.

Features

- Detects and limit the spread of smoke inside the building HVAC ducts
- Compatible with SensoIRIS B124 and SensoMAG B24 bases
- Easy to access box
- Transparent lid for device status visibility
- Sampling and outlet pipes included (27 cm)
- Mounting gasket included

Technical Specifications

	Airflow speed	From 1 to 20 m/s
	Material	Plastic (ABS)
	Color	White/Transparent
	Pipes material	Aluminum
1)	Pipe Lenght	27 cm
	IP protection	IP30
	Operating temperature	-10°C to +60°C
	Relative humidity resistance	(93 ± 3)% @ 40°C
	Box size	191x125x61 mm

Last update: 12/2024

