



The MC16-PAC-EX is multi-door physical access and building automation controller dedicated to the EX version of the RACS 5 v2 system. Depending on the version, it allows to control up to 16 read-in/out doors. MC16 can register events for Time & Attendance and can be integrated with intruder alarm systems. The integration enables a presentation of alarm zone status on terminal LEDs and to change zone status straight from a terminal. MC16 offers advanced and efficient methods for the management of users and their authorizations in the system. Controllers are configured in parallel and their total number does

not affect the total configuration time which usually is below 1 minute. Controllers are managed from VISO EX client-server Windows application operating with a centralized Microsoft SQL Server database. The system can be managed from multiple workstations by operators with various system rights. RACS 5 offers a software integration server and enables among others access to events and management of users. Communication between the PC and controller is fully encrypted using the AES128-CBC method and can be conducted either in LAN or WAN.

Features:

- 12 000 Access Credentials
- 8 Authentication Factors per Access Credential
- 100 Authorizations per Access Credential
- 16 read-in/out Access Doors
- 32 Access Points
- 64 Access Terminals (readers)
- 16 Access Zones
- 16 Alarm Zones
- 32 Automation Nodes
- 512 Authorizations
- 64 Rules within single Authorization
- 64 T&A Modes
- 16 Authentication Policies
- 4 steps within a single Authentication Policy
- 64 inputs (controller's mainboard, expanders, and terminals with I/Os)
- 64 outputs (controller's mainboard, expanders, and terminals with I/Os)
- 64 Function Keys
- 16 Global Commands
- Anti-passback and Timed anti-passback
- 32 Calendars
- 99 Periods within a single Calendar
- 250 Schedules
- 40 periods within a single Schedule
- 16 exceptions within a single Schedule
- direct operation with up to 16 MCT series terminals (RS 485 bus)
- operation with up to 16 OSDP terminals (OSDP v2 protocol) using MCI-3 interface
- direct operation with up to 4 PRT series terminals (RACS CLK/DTA bus)
- direct operation with up to 4 Wiegand terminals operation with PRT series and Wiegand terminals via MCX expanders
- 8 parametric EOL inputs onboard
- 6 transistors 15 V/150 mA outputs onboard
- 2 relay 30 V/1.5 A AC/DC outputs onboard
- 8 million event buffer on a memory card
- DC or AC supply
- backup battery charging and monitoring
- RACS CLK/DTA interface
- RS485 serial interface
- Ethernet interface
- AES128-CBC encrypted communication protocol
- quick configuration (below 1 minute)
- background configuration without a temporary system disabling the indoor environment
- built-in 12 VDC/1.0 A power supply unit
- dimensions: 72.0 x 175.0 x 30.0 mm (height x width x depth)
- CE mark

Features:

MC16-PAC-EX Versions																
Parameter	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Access Doors	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Access Points	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
Access Terminals	4	8	12	16	20	24	28	32	36	40	44	48	52	56	60	64
Access Zones	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
Alarm Zones	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
Power Supplies	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
Automation Nodes	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
Local Commands	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
Inputs	8	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96
Outputs	8	8	12	16	20	24	28	32	36	40	44	48	52	56	60	64
Function Keys	8	16	24	32	40	48	56	64	72	80	88	96	104	112	120	128
Access Credentials									12000							
Access Doors per Access Point									1							

Ordering guide

Item	Description
MC16-PAC-EX-1	Access controller board; 1-door license
MC16-PAC-EX-2	Access controller board; 2-door license
MC16-PAC-EX-3	Access controller board; 3-door license
MC16-PAC-EX-4	Access controller board; 4-door license
MC16-PAC-EX-N	Access controller board; N-door license (N=1-16)
MC16-PAC-EX-LIC-1	1-door license extension for MC16-PAC-EX access controller
MC16-UPG-STtoEX-LIC-1	1-door license to upgrade the controller from MC16-PAC-ST to MC16-PAC-EX

Legal Notice

This document is not intended to be a technical specification of the product and has informative character only. The Manufactures of product reserves right to change its characteristic without notice. The product features listed in this document refer to the entire series and depends on particular product version, configuration and additional equipment.

RevA © 2022 Roger sp. z o.o. sp. k. All rights reserved.

This document is a subject to the Terms of Use in their current version published at the www.roger.pl