

DEXIA

Cod. DXLA240042

**Introduction**

DEXIA series LED emergency light for centralized power supply system with self-extinguishing RAL9003 white polycarbonate body and ultrasound-welded self-extinguishing transparent polycarbonate screen. Wall, ceiling and flush mount installation. Power supply 220/230 Vac, 50-60 Hz. Luminous flux 700 lm. Protection rating IP42 or IP65 with accessory kit, double insulated, operating temperature 0 °C ÷ 40 °C. Dimensions: 322 x 140 x 50 mm.

Description

Product series	DEXIA
Product type	Emergency luminaire
Version	Central Battery (centralized power supply)
Type	-
Dimensions	Height 140 mm, Length 322 mm, Depth 50 mm

Technical specifications

Installation	Wall, ceiling, surface/false ceiling mount
Power supply	220/230 V~, 50-60 Hz
Absorbed power in W	7.5 W
Maximum absorbed power in VA	12 VA
Battery	-
Autonomy	-
Total charging time	-

Body	White Polycarbonate RAL9003
Glow wire	850 °C
Screen	Ultrasound-welded transparent Polycarbonate
IP Protection rating	IP42 (IP65 with accessory kit)
IK Protection rating	IK07
Insulation class	II
Operating temperature	0° - 40°C
Compliant to standards	EN 60598-1, EN 60598-2-22, EN 61547, EN 55015 EN 61000-3-2, EN 61000-3-3, EN 61347-1, EN 61347-2-7

Light source	LED
Colour temperature	6000K
Luminous flux	700 lm

