


DIVA

Cod. DVLA240042

**Introduction**

DIVA series LED emergency light for centralized power supply system with self-extinguishing RAL9003 white polycarbonate body and ultrasound-welded self-extinguishing transparent polycarbonate screen. Wall or ceiling installation. Power supply 220/230 Vac, 50-60 Hz. Luminous flux 400 lm. Protection rating IP42 or IP65 with accessory kit, double insulated, operating temperature 0 °C ÷ 40 °C. Dimensions: 100 x 230 x 22.5 mm.

Description

Product series	DIVA
Product type	Emergency luminaire
Version	Central Battery (alimentazione centralizzata)
Type	-
Dimensions	Height 100 mm, Length 230 mm, Depth 22.5 mm

Technical specifications

Installation	Wall, ceiling
Power supply	220/230 V~, 50-60 Hz
Absorbed power in W	5.8 W
Maximum absorbed power in VA	9.7 VA
Battery	-
Autonomy	-
Total charging time	-

Body	White Polycarbonate RAL9003
Glow wire	850 °C
Screen	Ultrasound-welded transparent Polycarbonate
IP Protection rating	IP42 (IP65 with accessory kit)
IK Protection rating	IK07
Insulation class	II
Operating temperature	0° - 40°C
Compliant to standards	EN 60598-1, EN 60598-2-22, EN 61547, EN 55015 EN 61000-3-2, EN 61000-3-3, EN 61347-1, EN 61347-2-7

Light source	LED
Colour temperature	6000K
Luminous flux	400 lm

