

This Article Information Sheet (AIS) provides relevant battery information to retailers, consumers, OEMs and others users requesting a GHS-compliant SDS. Articles, such as batteries, are exempt from GHS SDS classification criteria. The GHS criteria is not designed or intended to be used to classify the physical, health and environmental hazards of an article. Branded consumer batteries are defined as electrotechnical devices. The design, safety, manufacture, and qualification of branded consumer batteries follow ANSI and IEC battery standards. This document is based on principles set forth in the following hazard communication approaches: ANSI Z-400.1, GHS, JAMP AIS, IEC 62474, and ANSI C18.4M.

Duracell Nickel Metal Hydride (NiMH) Rechargeable Batteries
Duracell Nickel Metal Hydride (NiMH) Rechargeable Batteries packaged with/in equipment
(Duracell chargers/devices)
AIS-NIMH
15-Jan-20
6.a
Product Safety & Regulatory
1/7/2020
Duracell US Operations, Inc., 14 Research Drive, Bethel, CT USA 06801
www.duracell.com
North America: 1-800-551-2355 (9:00 AM - 5:00 PM EST)
ASIA: asiaconsumer.im@duracell.com
(UK) 0800 716434, (FR) 0800 346 790 Service & appel gratuits,
(IRL) 1 800 509 176, (DE) 800 101 2112, (AT) 0800 1025 1956,
(CH) 0800 000 885, (BE) 0800 509 95, (NL) 0800 265 8616,
(IT) 800 125 662, (ES) 900 800 522, (PT) 800 781 012,
(GR) 210 66 75 000, (CY) 22-210900, (DK) 78734857,
(SE) 0852503857, (FI) 0942705057, (NO) 63791957,
(ZA) 0800980782, (RO) 021 3361915, (MD) 022472402,
(BG) 02 40 24 500, (BIH) 033756000, (MNE) 020261920,
(PL) 22 692 42 77, (LT) (8) 37 401 111, (LV) 67798667,
(EE) 622 6360, (CZ) 224 826 323, (SK) 224 826 323,
(HU) 0620 770 7099, (HR) 0800 0009, (SI) 01/588 6800,
(AZ) 812 3100949, (UA) 044 490-97-71 (САВСЕРВІС СТОЛИЦЯ),
(KZ) +7 727 250 05 50, (TM) 00865 530070,
(KG) 0312 41 77 04 (Apple City International), (TR) 0 850 502 61 40.
Duracell branded consumer nickel metal hydride rechargeable battery
Electro-technical device
Portable power source for electronic devices
RECHARGEABLE
AA, AAA, C, D & 9V
HR6, HR03, HR9V, HR14, HR20
A battery powers a device by converting stored chemical energy into electrical energy.
DURACELL'
DURACELL RECHARGEABLE
FASTEST 50% Customs.
RECHARGEABLE STEAMS
CRAMPORTAL OF States
"1TRUSTED BRAND
BUMACELL
DUG BUG BUG BUG BUG BUG BUG BUG BUG BUG B
DURACEI DURACE
DURACELL DUR

AIS-NiMH 1 of 5



4. Article Construction	
Applicable Battery Industry	ANSI C18.2M Part 1, ANSI C18.2M Part 2, ANSI C18.4, IEC 61951-2, IEC 62133
Standards	ANSI C16.21VI Fait 1, ANSI C16.21VI Fait 2, ANSI C16.4, IEC 01951-2, IEC 02155
Electro-technical System	Nickel Metal Hydride
Anode (Electrode - Negative)	Metal hydride Metal hydride
Cathode (Electrode - Positive)	Nickel oxides
Electrolyte	Alkali Metal Hydroxide (aqueous potassium hydroxide - CAS # 1310-58-3)
Materials of Construction - Can	Nickel Plated Steel
Declarable Substances (IEC 62474	None - See Section 10b (EU REACH ANNEX XVII) of this document (page 4)
Criteria 1)	Notice - See Section 100 (EO REACH ANNEX XVII) of this document (page 4)
Mercury Free Battery (ANSI C18.4M <5ppm)	Yes
Small Cell or Battery	Size AAA fits inside a specially designed test cylinder 2.25 inches (57.1mm) long by 1.25 inches
(ANSI C18.1M Part 2; IEC 60086-5)	(31.70 mm) wide.
5. Health & Safety	
Ingestion/Small Parts Warning	Required for Battery Size AAA: Keep away from children. If swallowed, consult a physician immediately.
Normal Conditions of Use	Exposure to contents inside the sealed battery will not occur unless the battery leaks, is exposed to high temperatures, or is mechanically abused.
Note to Physician	A damaged battery will release concentrated and caustic potassium hydroxide.
First Aid - If swallowed	Do not induce vomiting. Seek medical attention immediately. For information on treatment, call 24-Hour National Battery Ingestion Hotline (telephone number below).
24-Hour National Battery Ingestion Hotline	USA/CANADA CALLS ONLY:: 800-498-8666
Poison Centers - World Directory	http://apps.who.int/poisoncentres
First Aid - Eye Contact	Flush with water for at least 15 minutes. Seek medical care if irritation persists.
First Aid - Skin Contact	Remove contaminated clothing. Wash skin with soap and water. Seek medical care if irritation persists.
First Aid - Inhalation	Remove to fresh air.
Battery Safety Standards & Testing	Duracell batteries meet the requirements of ANSI C18. 2M Part 2; IEC 61951-2, and IEC 62133. These standards specify tests and requirements for alkaline batteries to ensure safe operation under normal use and reasonably foreseeable misuse. The test regimes assess three conditions of safety. These are: 1-Intended use simulation: Partial use, vibration, thermal shock, and mechanical shock 2-Reasonably foreseeable misuse: Incorrect installation, external short-circuit, free fall (userdrop), over-discharge, and crush 3-Design consideration: Thermal abuse, mold stress
Precautionary Statements	(For AAA & Smaller) "CAUTION: Keep batteries away from children. If swallowed, consult a physician at once. For information on treatment, call (202) 625-3333 collect." (All sizes)" CAUTION: Never use different battery brands, types, capacities, or systems at the same time. For proper insertion, please observe pole indications (+/-). Duracell battery charger recommended. Keep batteries away from fire, or explosion may occur."
6. Fire Hazard & Firefighting	
Fire Hazard	Batteries may rupture or leak if involved in a fire.
Extinguishing Media	Use any extinguishing media appropriate for the surrounding area.
Fires Involving Large Quantities of Batteries	Large quantities of batteries involved in a fire will rupture and release caustic potassium hydroxide. Firefighters should wear self-contained breathing apparatus and protective clothing.
7. Handling & Storage	

AIS-NiMH 2 of 5



Avoid mechanical and electrical abuse. Do not short circuit or install incorrectly. Batteries may rupture or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions.
Store batteries in a dry place at normal room temperature. Refrigeration does not make them last longer.
Notify spill personnel of large spills. Irritating and flammable vapors may be released from leaking or ruptured batteries. Spread batteries apart to stop shorting. Eliminate all ignition sources. Evacuate area and allow vapors to dissipate. Clean-up personnel should wear appropriate PPE to avoid eye and skin contact and inhalation of vapors or fumes. Increase ventilation. Carefully collect batteries and place in appropriate container for disposal. Remove any spilled liquid with absorbent material and contain for disposal.
on 13)
Dispose of used (or excess) batteries in compliance with federal, state/provincial and local regulations. Do not accumulate large quantities of used batteries for disposal as accumulations could cause batteries to short-circuit. Do not incinerate. In countries, such as Canada and the EU, where there are regulations for the collection and recycling of batteries, consumers should dispose of their used batteries into the collection network at municipal depots and retailers. They should not dispose of batteries with household trash.
Nickel metal hydride rechargeable batteries are considered RCRA Universal Waste as long as they are recycled. In some states (California, New York, Minnesota, and Maine) Nickel metal hydride batteries must be recycled by state law.
California prohibits disposal of batteries as trash (including household trash).
n 14)
Nickel metal hydride (NiMH) batteries are not defined as dangerous goods under IATA, ICAO, and DOT. NIMH batteries packed in/with battery chargers, devices, or equipment are not regulated.
NIMH batteries, not shipped with/in devices or chargers, are defined as UN3496 dangerous goods under IMDG code for sea transportation with Special Provision (SP) SP177 and SP963 applicable.
•Nickel-metal hydride cells or batteries packed with or contained in equipment are not subject to the provisions of the IMDG Code. •All other nickel-metal hydride cells or batteries shall be securely packed and protected from short circuit. They are not subject to other provisions of this Code provided that they are loaded in a carge transport unit in a total quantity of less than 100 Kg gross mass. When loaded in a cargo transport unit in a total quantity of 100 Kg gross mass or more, they are not subject to other provisions of this Code except those of 5.4.1, 5.4.3 and column (16) of the dangerous good list in Chapter 3.2. •The requirements of the 5.4.1 & 5.4.3 sections and column (16) are: dangerous goods transport documentation to accompany the shipment, the shipment must be described as "UN3496, BATTERIES, NICKEL-METAL HYDRIDE, CLASS 9" on the shipper's declaration for dangerous goods. The dangerous goods description must also be entered on the Dangerous Cargo Manifest and/or the detailed stowage plan in compliance with the IMDG Code requirements for shipboard documentation. Stowage away from sources of heat.

AIS-NiMH 3 of 5



UN Identification Number/ Shipping Name	UN3496 - Batteries, Nickel Metal Hydride
Special Provision (SP) Conformance	Special regulatory provisions require batteries to be packaged in a manner that prevents the generation of a dangerous quantity of heat and short circuits. Shippers can prepare batteries by taping the terminals, individually packaging batteries, or otherwise segregating the batteries to prevent risk of creating a short circuit. Batteries shipped in original unopened Duracell packaging is compliant.
Internation Maritme Dangerous Goods (IMDG)	CODE: UN-3496, SP-117 & SP-963 [2018 EDITION]
US DOT SP	49 CFR 172.102 Special Provisions 130 and 340
Air Transport (IATA/ICAO) SP	Special Provision A199 (IATA 61th Edition - 2020). NOTE: The words "NOT RESTRICTED" and "SPECIAL PROVISION A199" must be included on the description of the substance on the Air Waybill when air way-bill is issued.
Passenger Air Travel	No restrictions
Emergency Transportation Hotline	CHEMTREC 24-Hour Emergency Response Hotline Within the United States call +703-527-3887 Outside the United States, call +1 703-527-3887 (Collect)
10. Regulatory Information (GHS Sect	ion 15)
10a. Battery Requirements	
USA EPA Mercury Containing & Rechargeable Battery Management Act of 1996	During the manufacturing process, no mercury is added.
EU Battery Directive 2006/66/EC & amendment 2013/56/EU	Compliant with marking and substance restrictions for mercury (<0.0005%); cadmium (<0.0020%)I and lead (<0.0040%). Global labels are marked with the special collection symbol and the EU qualifier in accordance with EU Battery Directive 2006/66/EC, Article 11, Paragraph 1 on batteries and accumulators and waste batteries and accumulators (Annex II).
10b. General Requirements USA CPSIA 2008 (PL. 11900314)	Exempt
· · · · · · · · · · · · · · · · · · ·	
USA CPSC FHSA (16 CFR 1500) USA EPA TSCA Section 13 (40 CFR 707.20)	Consumer batteries are not listed as a hazardous product. For customs clearance purpose, batteries are defined as an "Article".
USA EPA RCRA (40 CFR 261)	Nickel metal hydride rechargeable batteries are considered RCRA Universal Waste as long as they are recycled. In some states (California, New York, Minnesota, and Maine) Nickel metal hydride batteries must be recycled by state law.
California Prop 65	No warning required per 3rd party assessment.
CANADA Products Containing Mercury Regulations SOR/20140254	Mercury free
EU REACH REGULATION (EC) NO. 1907/2006	Regulated as an "article." No listed substances are present (>0.1% w/w) in accordance with ECJ article definition of 10 September 2015. If needed, a declaration (DoC) confirming the current SVHC Candidate List can be downloaded from the Duracell web site (https://www.duracell.com/en-us/forbusiness/) Folder: "Environmental & Regulatory."
EU REACH Annex XVII	The use of nickel in batteries does not meet the conditions of restriction described for Annex XVII Item #27 - Nickel. The use restriction applies for articles intended to come into direct and prolonged contact with the skin, specifically pierced earning posts and other types of jewelry.
EU REACH Article 31	SDS is not required consumer alkaline batteries.
40. D	
10c. Regulatory Definitions - Articles	
10c. Regulatory Definitions - Articles USA OSHA	29 CFR 1910.1200(b)(6)(v)
USA OSHA	29 CFR 1910.1200(b)(6)(v) 40 CFR 704.3; 710.2(3)(c); and [19 CFR 12.1209a)]
	29 CFR 1910.1200(b)(6)(v) 40 CFR 704.3; 710.2(3)(c); and [19 CFR 12.1209a)] Title 1 - Chapter 2 - Article 3(3)

AIS-NiMH 4 of 5



11. Other Information

ANSI Z 400.1/Z19.1 (2010)

AIS Hazard Communication Approach	es (consulted in developing this document):
Globally Harmonized System (GHS)	GHS SDS requirements and classification criteria do not apply to articles or products (such as batteries) that have a fixed shape, which are not intended to release a chemical. The article exemption is found in Section 1.3.2.1.1 of the GHS and reads: The GHS applies to pure substances and their dilute solutions and to mixtures. "Articles" as defined by the Hazard Communication Standard (29 CFR 1900.1200) of the OSHA of the USA, or by similar definition, are outside the scope of the system."
Joint Article Management Promotion Consortium JAMP	JAMP is a Japanese Industry Association who developed the concept of an Article Information Sheet as a supply chain tool to share and communicate chemical information in articles. The AIS authoring process is based on "declarable" substances to meet global regulatory requirements as well as substances to be reported by GADSL, JIG, etc.
IEC 62474 Ed. 1.0 B:2012 Material Declaration for Products of and for the Electro-technical Industry	An international standard that came into effect in March 2012 concerning declaration for electrical and electronic products. IEC 6274 replaces the defunct Joint Industry Guide – Material Declaration for Electro-technical Products (JIG-101-Ed 4.1 (May 21, 2012)
IEC 62474 Database - Publically available online (maintained by TC11: Environmental Standardization for electrical and electronic products and systems.	The general principle for a substance to be included in the database as a declarable substance is: 1) existing national laws or regulations in an IEC member country that are relevant to Electro-technical products and that prohibit or restrict substances, or that have a labeling, communication, reporting or notification requirement, and 2) applying IEC 62474 criteria results in identification of declarable substance.
ANSI C18.4M-2017 Portable Cells and Batteries - Environmental	This standard provides regulatory guidance and a template to author an article information sheet for a portable consumer battery. See Annex (Informational) C.2 Safety Data Sheets and Annex E (Informative) E.2 General.

DISCLAIMER: This AIS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by Duracell to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations. This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. Duracell assumes no responsibility for injury to the recipient or third persons or for any damage to any property resulting from misuse of the product.

may be acceptable for International use.

2.1 Scope: Applies to preparation of SDSs for hazardous chemicals used under occupational conditions. Does not address how the standard may be applied to articles. It presents basic information on how to develop and write a SDS. Additional information is provided to help comply with state and federal environmental and safety laws and regulations. Elements of the standard

AIS-NiMH 5 of 5