

**HARPER 100**

Cod. HP100LA110040

**Introduction**

HARPER100 series LED emergency light for centralized power supply system with self-extinguishing RAL9003 white polycarbonate body and PMMA reflector with no photobiological risk (RG0). Wall, ceiling and flush mount installation. Power supply 220/230 Vac, 50-60 Hz. Luminous flux 130 lm. Protection rating IP40, double insulated, operating temperature 0 °C ÷ 50 °C. Dimensions: 122 x 255 x 38 mm.

**Description**

|                |                                            |
|----------------|--------------------------------------------|
| Product series | HARPER 100                                 |
| Product type   | Emergency luminaire                        |
| Version        | Central Battery (centralized power supply) |
| Type           | -                                          |
| Dimensions     | Height 122 mm, Length 255 mm, Depth 38 mm  |

**Technical specifications**

|                             |                                            |
|-----------------------------|--------------------------------------------|
| Installation                | Wall, ceiling, surface/false ceiling mount |
| Power supply                | 220/230 Vac, 50-60 Hz                      |
| Absorbed power in W         | 3 W                                        |
| Current absorbed from Mains | 5 VA                                       |
| Battery                     | -                                          |
| Minimum autonomy            | -                                          |
| Total charging time         | -                                          |

|                       |                             |
|-----------------------|-----------------------------|
| Body                  | White Polycarbonate RAL9003 |
| Glow wire             | 850 °C                      |
| Diffuser              | PMMA laser finish           |
| IP Protection rating  | IP40                        |
| IK Protection rating  | IK07                        |
| Insulation class      | II                          |
| Operating temperature | 0° - 50°C                   |

|                        |                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------|
| Compliant to standards | EN 60598-1, EN 60598-2-22, EN 61547, EN 55015<br>EN 61000-3-2, EN 61000-3-3, EN 61347-1, EN 61347-2-7 |
| Photobiological risk   | RG0 (exempt) according to EN 62471                                                                    |

|                    |        |
|--------------------|--------|
| Light source       | LED    |
| Colour temperature | 6000K  |
| Luminous flux      | 130 lm |

