


HARPER 100

Cod. HP100LA110065

**Introduction**

HARPER100 series LED emergency light for centralized power supply system with self-extinguishing RAL9003 white polycarbonate body and PMMA reflector with no photobiological risk (RG0). Wall, ceiling and flush mount installation. Power supply 220/230 Vac, 50-60 Hz. Luminous flux 130 lm. Protection rating IP65, double insulated, operating temperature 0 °C ÷ 50 °C. Dimensions: 122 x 255 x 38 mm.

Description

Product series	HARPER 100
Product type	Emergency luminaire
Version	Central Battery (centralized power supply)
Type	-
Dimensions	Height 122 mm, Length 255 mm, Depth 38 mm

Technical specifications

Installation	Wall, ceiling, surface/false ceiling mount
Power supply	220/230 Vac, 50-60 Hz
Absorbed power in W	3 W
Current absorbed from Mains	5 VA
Battery	-
Minimum autonomy	-
Total charging time	-

Body	White Polycarbonate RAL9003
Glow wire	850 °C
Diffuser	PMMA laser finish
IP Protection rating	IP65
IK Protection rating	IK07
Insulation class	II
Operating temperature	0° - 50°C

Compliant to standards	EN 60598-1, EN 60598-2-22, EN 61547, EN 55015 EN 61000-3-2, EN 61000-3-3, EN 61347-1, EN 61347-2-7
Photobiological risk	RG0 (exempt) according to EN 62471

Light source	LED
Colour temperature	6000K
Luminous flux	130 lm

