



HP200

description	Product range	HARPER 200		
	Product type	Emergency lamp		
	Versions	Standard, Self-Test, Bus-Supervised, Central-Battery		
	Type	Maintained, Non-Maintained		
technical specifications	Installation	Wall, ceiling, flush mounting/false ceiling		
	Power supply	220/230Vac, 50-60Hz		
	Battery	LiFePO ₄ 3,2V		
	Insulation class	II		
	Colour	RAL9003 white		
	Light source	LED		
	Colour temperature	6000K		
	Additional info	Dedicated terminal for inhibition function		
		Dedicated terminal for rest mode		
		Test button		
	IP grade	IP42, IP65		
	IK grade	IK07		
	Operating temperature	From 0° to 50°C		
	Compliant to standards	EN 55015, EN 60598-1, EN 60598-2-22,		
		EN 61000-3-2, EN 61000-3-3, EN 61347-1,		
EN 61347-2-7, EN 61547, EN 62471				
dimensions (mm)	Width	319		
	Height	137		
	Depth	38		
others informations	Guarantee	5 years		
	Packaging	10 pieces		
Accessories	OH200BRI Wall box for flush mounting		OH100FCK Plasterboard and false ceiling fastening kit	
	OH200PTDW Pictogram for HP200 indicating down *		OH100GRT Metal protective grating for complete protection of the luminaire body	
	OH200PTDX Pictogram for HP200 indicating right *		INICOM Controller for the remote management of rest mode	
	OH200PTSX Pictogram for HP200 indicating left*			

* See the "Accessories and spare parts" section.

* See the "Accessories and spare parts" section.

available versions	Order codes	Power*	Duration	Battery LiFePO ₄ 3,2V [Ah]	Maintained Non- Maintained	N/M FLUX (lm)	M FLUX (lm)	IP Grade	Recharge
standard	 HP200 S E 11 02 42	11W	1,5 h	1,5	N/M	180	-	IP42	12h
	 HP200 S E 24 01 42	24W	1 h	1,5	N/M	360	-	IP42	12h
	 HP200 S E 11 05 42	11W	4 h	3,3	N/M	180	-	IP42	24h
	 HP200 S E 24 02 42	24W	2 h	3,3	N/M	360	-	IP42	24h
	 HP200 S E 11 02 65	11W	1,5 h	1,5	N/M	180	-	IP65	12h
	 HP200 S E 24 01 65	24W	1 h	1,5	N/M	360	-	IP65	12h
	 HP200 S E 11 05 65	11W	4 h	3,3	N/M	180	-	IP65	24h
	 HP200 S E 24 02 65	24W	2 h	3,3	N/M	360	-	IP65	24h
self-test	 HP200 A E 18 01 42	18W-11W	1h-1,5h	1,5	N/M	180-135	-	IP42	6h
	 HP200 A E 36 01 42	36W-24W	1h-1,5h	3,3	N/M	360-270	-	IP42	12h
	 HP200 A E 18 03 42	18W-11W	3h-4h	3,3	N/M	180-135	-	IP42	12h
	 HP200 A E 36 03 42	36W-24W	3h-4h	2 x 3,3	N/M	360-270	-	IP42	24h
	 HP200 A A 18 01 42	18W-11W	1h-1,5h	1,5	N/M-M	180-135	80	IP42	6h
	 HP200 A A 36 01 42	36W-24W	1h-1,5h	3,3	N/M-M	360-270	170	IP42	12h
	 HP200 A A 18 03 42	18W-11W	3h-4h	3,3	N/M-M	180-135	80	IP42	12h
	 HP200 A A 36 03 42	36W-24W	3h-4h	2 x 3,3	N/M-M	360-270	170	IP42	24h
	 HP200 A E 18 01 65	18W-11W	1h-1,5h	1,5	N/M	180-135	-	IP65	6h
	 HP200 A E 36 01 65	36W-24W	1h-1,5h	3,3	N/M	360-270	-	IP65	12h
	 HP200 A E 18 03 65	18W-11W	3h-4h	3,3	N/M	180-135	-	IP65	12h
	 HP200 A E 36 03 65	36W-24W	3h-4h	2 x 3,3	N/M	360-270	-	IP65	24h
	 HP200 A A 18 01 65	18W-11W	1h-1,5h	1,5	N/M-M	180-135	80	IP65	6h
	 HP200 A A 36 01 65	36W-24W	1h-1,5h	3,3	N/M-M	360-270	170	IP65	12h
	 HP200 A A 18 03 65	18W-11W	3h-4h	3,3	N/M-M	180-135	80	IP65	12h
	 HP200 A A 36 03 65	36W-24W	3h-4h	2 x 3,3	N/M-M	360-270	170	IP65	24h
bus-supervised	 HP200 B E 18 01 42	18W-11W	1h-1,5h	1,5	N/M	180-135	-	IP42	6h
	 HP200 B E 36 01 42	36W-24W	1h-1,5h	3,3	N/M	360-270	-	IP42	12h
	 HP200 B E 18 03 42	18W-11W	3h-4h	3,3	N/M	180-135	-	IP42	12h
	 HP200 B E 36 03 42	36W-24W	3h-4h	2 x 3,3	N/M	360-270	-	IP42	24h
	 HP200 B A 18 01 42	18W-11W	1h-1,5h	1,5	N/M-M	180-135	80	IP42	6h
	 HP200 B A 36 01 42	36W-24W	1h-1,5h	3,3	N/M-M	360-270	170	IP42	12h
	 HP200 B A 18 03 42	18W-11W	3h-4h	3,3	N/M-M	180-135	80	IP42	12h
	 HP200 B A 36 03 42	36W-24W	3h-4h	2 x 3,3	N/M-M	360-270	170	IP42	24h
	 HP200 B E 18 01 65	18W-11W	1h-1,5h	1,5	N/M	180-135	-	IP65	6h
	 HP200 B E 36 01 65	36W-24W	1h-1,5h	3,3	N/M	360-270	-	IP65	12h
	 HP200 B E 18 03 65	18W-11W	3h-4h	3,3	N/M	180-135	-	IP65	12h
	 HP200 B E 36 03 65	36W-24W	3h-4h	2 x 3,3	N/M	360-270	-	IP65	24h
	 HP200 B A 18 01 65	18W-11W	1h-1,5h	1,5	N/M-M	180-135	80	IP65	6h
	 HP200 B A 36 01 65	36W-24W	1h-1,5h	3,3	N/M-M	360-270	170	IP65	12h
central-battery	 HP200 B A 18 03 65	18W-11W	3h-4h	3,3	N/M-M	180-135	80	IP65	12h
	 HP200 B A 36 03 65	36W-24W	3h-4h	2 x 3,3	N/M-M	360-270	170	IP65	24h
	 HP200 L A 18 00 42	18W	-	-	-	-	180	IP42	-
	 HP200 L A 36 00 42	36W	-	-	-	-	360	IP42	-
	 HP200 L A 18 00 65	18W	-	-	-	-	180	IP65	-
	 HP200 L A 36 00 65	36W	-	-	-	-	360	IP65	-

* It is possible to choose between two power values (where indicated) during the installation phase.