


MC 746-E

Magnetic Contact Surface mount, NC/NO

Technical data

Installation method	Surface mount
Contact function	Change-over (NC/NO)
Contact rating	48 VDC / 250 mA / 5 VA
Magnet type	Alnico 5
Mounting on steel	Not recommended
Make distance (wood) mm	37
Make distance (steel) mm	X
Tamper protection	Yes
Connection	Cable
Housing material	ABS Plastic
Operating temperature range	-40°C - +70°C
Housing protection class	IP 67
Contact dimensions (L x W x H) mm	60 x 14 x 5
Magnet dimensions (L x W x H) mm	60 x 14 x 5
Grade	2



MC 746 is a small and thin magnetic contact with change-over (NC/NO) function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening.

Both the contact and the magnet part are in a water proof (IP 67) plastic housing. The small and thin format makes it especially easy to install in limited spaces, e.g. on shutters and drawers. With lid for the screw holes.

ORDERING INFORMATION

Model	Description
MC 746 -E	Magnetic contact, NC, surface mount, 2 m cable
MC 746-E-6	Magnetic contact, NC, surface mount, 6 m cable
MC 746-E-10	Magnetic contact, NC, surface mount, 10 m cable