

Panda Wireless Keypad for LightSYS



The Panda wireless keypad is RISCO Group's latest, highly reliable 2-way wireless keypad with a clean design, ideal for users looking for a contemporary look and feel in their premises. Due to its tactile and durable keys, it provides great reliability and responsiveness. It is easy to operate either by using the keypad itself or a proximity tag.

The Panda wireless is a true 2-way keypad, which receives real time status indication (auto-status) from the panel on cloud connectivity, trouble and alarm. When the keypad is not in use, it enters into battery saving mode.

The keypad is designed for quick and easy installation, with incorporated mounting bracket and one screw fixation of the keypad to the mounting bracket.

In addition, the Panda wireless keypad has a flush mount accessory for smooth and discreet installation on the wall.

The keypad is suitable for various residential and commercial applications, and offers a perfect opportunity to upgrade an existing installation with a stylish face-lift.



Features

- Compatible with LightSYS2 firmware version 5.87 and above
- Responsive and reliable due to tactile and durable keys
- Wall and cover tamper protection
- Easy to install with incorporated mounting bracket and one screw fixation of the keypad to the mounting bracket
- Visual on-screen indicators for Cloud Connectivity, System Trouble, Tamper and Arm/Disarm
- Model: RW432KPP
- Flush mount kit: RA332KPFM

Technical Specifications

- Current Consumption: Standby current 9 μ A, Max current 150 mA
- Battery Type CR123, 3V Lithium battery (x 4)
- Typical Battery Life 3 years
- Frequency 433.92 and 868.65 MHz
- Proximity RF frequency 13.56 MHz
- Dimensions (H x W x D): 178 x 103 x 38 mm (7.0 x 4.0 x 1.5)
- Weight (Including batteries) 0.435 kg
- Operating temperature -10°C to 55°C (14°F to 131°F)
- Storage temperature -20°C to 70°C (-4°F to 158°F)