

Redscan Manager release notes

As of 21-May-2019

Firmware Version	Date of release	
Ver 1.0.0	10-Feb-16	First production model. For RLS-2020I only
Ver 1.0.1.1	25-Feb-16	Can change the unit from "m" to "feet". Correct the adjustable range for Auto area adjustment from 1-20m (3.3-65ft) to 0-20m (0-65ft.)
Ver 1.0.3.4	11-Jul-16	Bug fix XY Cordinate indication Uptate Help file
Ver 5.0.1.0	11-Nov-16	Compatible with RLS-2020S. Change the procedures for Import and Export function. Bug fix. And, amended help file.
Ver 6.0.2.3	8-Dec-16	Compatible with RLS-3060L/SH (F/W ver. 7.0.0 or later)
Ver 6.0.2.3 a	5-Jan-17	Eliminated unnecessary file from its installer
Ver 8.0.0.0	4-Apr-18	Added functions added in RLS-3060 V 8.0.0 or later. * RLS-3060SH V8.0.0 or later : Added detection expansion function, Added terminal settings * RLS-3060L V8.0.0 or later : Activate some functions of SH with L, Added terminal settings <u>Can select language from the options English French German Spanish Italian or Portuguese</u>
Ver 8.1.0.0	28-May-18	Expansion of the range for the response time of RLS-2020S/I V.1.6.0 to max. 900,000 msec (15 minutes) for <u>longer period loitering detection</u>
Ver 8.2.2.0	1-Oct-18	Added functions added in RLS-2020S/I V 2.1.0 * <u>Multiple relay outputs can be assigned for alarm, trouble (AM/AR/SO/DQ/TR/TA) and device monitoring</u>
Ver 8.3.0.0	15-May-19	Undo function for detection area setting for RLS-3060 and RLS-2020 Compatible with RLS-2020 firmware version 3.0.0 Correct the drawing detection area in H1 mode for RLS-3060 Compatible with RLS-3060 firmware version 8.1.0 (Future used)