

SC-32-0220-0001-99

SmartCell White Sounder and Wall-Beacon (VAD White Flash)

Overview

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include part 23 VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-32-0220-0001-99

SmartCell White Sounder and Wall-Beacon (VAD White Flash)

Technical specifications

General

Wireless frequency	868 MHz
--------------------	---------

Sounder

Output level	95 dB(A) at 1 m max.
--------------	----------------------

Output level adjustment	High or low
-------------------------	-------------

Selectable tones	32
------------------	----

VAD

Colour	white flash
--------	-------------

Rating	W-2.4-6
--------	---------

Flash frequency	0.5 Hz (1 flash, every 2 seconds)
-----------------	-----------------------------------

Physical

Physical dimensions	110 x 77 mm (Ø x D)
---------------------	---------------------

Net weight	0.2 kg
------------	--------

Colour	White
--------	-------

Mounting type	Wall mount
---------------	------------

Mounting position	Wall
-------------------	------

Batteries	3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)
-----------	--

Environmental

Operating temperature	-10 to +55°C
-----------------------	--------------

Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
---------------------	---

Relative humidity	95% noncondensing max.
-------------------	------------------------

Environment	Indoor
-------------	--------

IP rating	IP21C
-----------	-------

Standards & regulation

Compliance	CE
------------	----

Certification	CPR
---------------	-----

Standards	EN54-3 EN54-13 EN54-23 EN54-25
-----------	---

