

DS-PDMCS-EG2-WE Wireless Slim Magnet Detector

DS-PDMCS-EG2-WE is a wireless opening detector that notifies of first signs of room intrusion by means of a broken door or window, slim design specially used in window frames for vanishing installation.

Key Features

- Slim design for an unobtrusive (unnoticeable) installation
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission

Detection Gap

Table 1.

Axes of Operation	Event	Without Nominal Distance	With Nominal Distance 5 mm
		Distance in Air	Distance in Air
X+	Remove	20	20
	Approach	23	26
X-	Remove	12	14
	Approach	16	20
Y	Remove	42	37
	Approach	35	30
Z+	Remove	50	48
	Approach	43	42
Z-	Remove	52	52
	Approach	46	46

Available Model

DS-PDMCS-EG2-WE





Specification

DS-PDMCS-EG2-WE				
	Reed switch	1		
Technical characteristics	Tamper protection	Front and back		
	LED indicator	Alarm (blue)		
	Wireless technology	Tri-X Wireless Technology		
	Two-way wireless communication	Supported		
	Transmission frequency	868 MHz		
	RF range	1200 m (open space)		
Wireless technical characteristics	Transmission encryption	AES-128 encryption		
Citalacteristics	Enrolling methods	Power up, remote ID and QR code		
	Frequency hopping	Multichannel transmission		
	Signal strength indicators	Supported		
	Environment temperature indicator	Supported		
Floorise Lond bottom	Battery	CR2450 x 1 (included)		
Electrical and battery	Standard battery life	3 years		
	Dimension (W × H × D)	29mm × 69mm × 10mm 14mm × 69mm × 10mm		
Environmental and	Weight	38 g		
operating features	Storage temperature	-20 °C to 60 °C (-4 °F to 140 °F)		
	Operating temperature	-10 °C to 55 °C (14 °F to 131 °F)		
	Operating humidity	10% to 90%		



Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400

sales.usa@hikvision.com **Hikvision Australia** T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T+01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com