

DS-PDP15P-EG2-WE Wireless PIR Detector

DS-PDP15P-EG2-WE is a fully supervised two-way wireless detector featuring motion detection, tamper protection, low battery and supervision. It can operate for up to 5 years from an in-built battery, and monitors the area within 15 m radius, ignores animals while recognizing human from the first step.





Key Features

- SEC (Smart Environmental Control) - Advanced digital signal processing and 3D optics
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Easy replaceable battery with PCB protected
- Frequency hopping against jamming for reliable transmission



Lens Diagram



- (a) Detection Range
- 85.9°
- 52 zones
- 4 planes

Available Model

DS-PDP15P-EG2-WE

Specification

DS-PDP15P-EG2-WE

Technical characteristics	Detection range	15m
	Coverage angle	85.9°
	Detection speed	0.3 to 2 m/s
	Auto sensitivity	Supported
	Pet immunity	Up to 30Kg
	Digital temperature compensation	Supported
	Technology	Digital microprocessor based
	Sealed optics	Supported
	Creep zone protection	Supported
	Direct light filter	6500 lux
	Tamper protection	Front & Back
	LED indicator	Alarm (blue)
Encapsulated PCB	Supported	
Wireless technical characteristics	Wireless technology	Tri-X Wireless Technology
	Environment temperature Indicator	Supported
	2-way wireless communication	Supported
	Transmission frequency	868 MHz
	Frequency hopping	Multichannel transmission
	Transmission encryption	AES-128 encryption
	Signal strength indicators	Supported
	RF range	1600m (open area)
Electrical and battery	Enrolling methods	Power up, Remote ID, QR code
	Battery	CR123A x 1 (included)
Environmental and operating features	Standard battery life	5 years
	Operating temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operating humidity	10% to 90%
	Dimension (W× H × D)	65.5 mm (2.58 ") × 103mm (4.06 ") × 48.5 mm (1.91 ")
Mounting	Weight	128g (4.5 oz)
	Bracket	Optional wall & ceiling accessory
	Installation height	1.8 m to 2.4 m

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
sateru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com