

Hik-Connect Mobile Client SPEC V4.5.0

Software Information


Name: Hik-Connect Mobile Client Software

Version: V4.5.0

Android:

System Requirement: Android 4.4 or later **iOS**:

System Requirement: iOS 8.0 or later



Introduction

The Hik-Connect App is designed for managing Hikvision products, including DVRs, NVRs, cameras, video intercom devices, and security control panels, etc. With the app, you can view real-time surveillance video or play it back at any place where Wi-Fi, 3G, or 4G networks are available. When alarms of your devices are triggered, you can get instant notifications on the App.

The App also supports functionality related with Hik-ProConnect, which is a platform for Installers in the security industry to manage end user's devices. On the App, you can grant permissions to a specific Installer to allow the Installer to provide installation and maintenance services for you.

Key features

- Account management
- Adds devices via scanning QR code
- Adds devices via IP/Domain
- Adds devices via Hik-Connect Domain.
- Multiple window division modes: 1-division, 4-division, 9-division, 12-division, and 16-division

- Adds devices to the Favorites folder
- Two-way audio intercom
- Videos and pictures encryption
- Changes image qualities
- PTZ control
- 8X digital zoom
- Playback of 4 cameras simultaneously
- Pictures and videos management
- Instant alarm notifications with pictures and videos
- Updates devices remotely
- Answers calls from doorbells/video intercom devices
- Arms security control panel remotely
- Shares devices to others and grants operation permissions to them
- Login by fingerprint/face ID
- Hik-ProConnect site management

Functional Parameters

Account Management	Register a new account via email address or mobile phone number		
	Account login and logout		
	 Account information settings 		
	Changing account password		
	Retrieving password		
	Visitor mode		
	 Login by fingerprint 		
	1/4/9/12/16 window division		
	Audio control		
	Max. 8X digital zoom		
	Capture and recording		
Live View	Full-screen mode		
Live view	Two-way audio		
	Change live view quality		
	Enable fisheye mode		
	➢ Hardware decoding (Only supported by devices added via		
	IP/Domain)		
	Control PTZ		
	Zoom in and out		
	Adjust PTZ speed		
PTZ	Control focus and iris		
	Set and call preset		
	 Auto Scan (The device should support the function) 		
	 Auto-Tracking (The device should support the function) 		
Playback	Search videos by time for playback		

	N	A window division mode for playback simultaneously		
	A (4-window division mode for playback simultaneously		
		Control audio		
		Capture and recording		
		Drag timeline to set playback start time		
		Hardware decoding		
		Event playback		
		Add and deleting device		
		Support adding the devices which support Hik-Connect		
		service (hereafter simplified as "Hik-Connect device" via Hik-		
		Connect domain or scanning QR code		
		Support adding devices via IP/Domain		
		• Support adding detected online devices which are in the same		
		local area network with the phone or tablet		
	\triangleright	Edit device name and channel name.		
	\triangleright	Display storage status and device version (for Hik-Connect Devices)		
	\triangleright	Detect device version and remotely upgrading		
	≻	Videos and pictures encryption (for Hik-Connect Devices)		
	≻	Share channels to other account		
Device Management	≻	Set partition and zones (for security control panel)		
	≻	Unbind devices from other accounts with devices' password		
	\triangleright	Reset devices' password		
	\triangleright	Remotely Configure devices		
	\triangleright	Change device verification code		
	\triangleright	Set DDNS (Only supported by devices added via Hik-Connect		
		Domain or Scanning QR Code)		
	\succ	Transfer devices to another's account		
	\triangleright	Share device(s) to other users		
	\succ	Add devices to Favorites		
	\succ	Draw motion detection area for specific network cameras		
	\succ	Configure audio and strobe light alarm, light settings, PIR detection		
		are for Floodlight camera		
	\triangleright	View the details of the sites that you own, including site name,		
		devices on the each site, and information of the Installer who is		
		managing the devices of the site		
	≻	View history linkage, which refers to the process in which an event		
		detected by device A triggers actions of device B, device C, device		
Hik-ProConnect Related Functionality		D, and so forth		
	≻	View external linked videos, which refers to the video recorded by		
		the linked device of the alarm-source		
	≻	Edit permissions authorized to the Installer		
	≻	Hand over a specific site to another end user or to an Installer		
	\triangleright	Cancel all authorizations to the Installer		

	Add a specific device, which has already been added to the app, to
	a specific site, by authorizing the device to the Installer
	Enable/disable Alarm Receiving Center (ARC) service for a specific device
	Receive site permission applications from the Installer
	> Receive notifications about the Installer's relinquishment of site
	permissions or device permissions
	Display authorization status of a specific device on the device list
	\succ Display the logo of a specific Installer on the loading page and
	About page
	Arm and disarm remotely
	 Receive alarm (event) notifications
Alarm Notification	 View alarm (event) information, related pictures, and related videos
	 (Thermal binoculars) View alarm-related optical mode picture and thermographic mode picture.
	 Supports two notification modes: "Receive Events and Push
	Notifications" and "Receive Events but Not Push Notifications"
	 Receive notifications hen others call
	 Remotely acceptor declining the call (for doorbells)
	 Remotely open/close door.
	 View call logs
	 Switch scenes (Stay, Away, Sleep, and Custom) for indoor stations
Video Intercom	of the upcoming versions of KH8350, KH8520, and KH6320 series
	 View live video streamed from the camera linked to the door
	station
	 Control two-way audio
	 Play back video footage from the camera linked to the door station
	View related events of the latest 7 days
	 Configuration of the partitions (areas), detectors and sensors, etc.
	 Stay arm/Away arm/Disarm
	 Clear alarms
Security control panels	Receive alarm notifications
	Bypass some zones
	\succ Other functions such as faults check and wireless device
	supervision (only supported by specific security control panels)
Access Control	Remotely control doors
	 Configure access control devices
Facial Data Management	Upload facial data to DeepinMind servers and delete facial data.
AcuSense Series NVR	Add up to 4 areas to the NVR.
(only for Australian	Arm/disarm area(s).
market)	Automatically arm/disarm a specific area.

	 Clear alarm(s). 	
	Link AcuSense cameras to the NVR.	
	View Live video streamed from the cameras linked to the NVR.	
	Set the cameras linked to the NVR.	
	Manage local pictures and videos	
Pictures and Videos	View pictures and playing videos	
Management	Download pictures and videos to the phone	
	Share pictures and videos to others	
System Settings	 Enable push notification 	
	Enable/disable saving device parameters	
	Enable/disable hard-decoding preferred	
	Enable auto-receiving alarm (event) information when the phone is	
	powered on	
	View traffic statistic	
	Resume latest live view	
	Display floating live view on the device list	
	Display channel-zero	
	Reset password for DVR and NVR	
	> Set Wi-Fi	
	New versions online detection	
	Help and feedbacks	
Language	Simplified Chinese, English, Russian, Estonian, Bulgarian,	
	Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish,	
	Dutch, Portuguese, Spanish, Romanian, Danish, Swedish,	
	Norwegian, Finnish, Croatian, Slovenian, Serb, Turkish, Korean,	
	Traditional Chinese, Thai, Vietnamese, Japanese, Hebraism,	
	Latvian, Lithuanian, Brazilian Portuguese, Arabic, Farsi, Indonesian,	
	Uzbek, Kazak	

Technical Parameters

Item	Parameters
Max. Connected Devices (Hik-Connect Domain)	1024
Max. Channels Can Be Selected for Live View or	256
Playback	
Max. Shared Accounts (By One Channel)	64
Max. Streaming Number (One channel/ Live	20
View)	
Max. Cameras for Live View Simultaneously	16
Max. Cameras for Playback Simultaneously	4 (*supported model only)
Max. Favorites Folders	32
Max. Users for Receiving Shared Devices	100
Video Encoding	H.264,MPEG4,MJPEG,
	H.264+,H.265,H.265+

Item	Parameters
Audio Encoding	G711_A,G711_U,AAC
Compatible Devices	DVRs, NVRs, cameras, video intercom
	devices and security control panels with
	Hik-Connect Function.