

Adhesion Promoter

Cleaner/Degreaser/Primer

General Description

Adhesion Promoter is a cleaner, degreaser and primer which will activate non porous surfaces such as plastics, coatings and metals for improved adhesion of sealants (based on silicone, polyurethane and MS-Polymers), and adhesives (based on MS or Hybrid technology, polyurethanes, structural acrylics and tapes). For Polypropylene substrates, use Tradeprime PP.

Application Examples

Preparation of plastics, powder-coatings and other non-porous surfaces before bonding and sealing.

Physical Data

Base	Solvents and priming agents
Colour	Colourless (as water)
Specific gravity	0.78 @ 20°C
Flammability	Highly flammable
Flash point	13°C
Storage life	12 months. Store in a flame-proof room between 5°C and 25°C.
Packaging	Metal tin of 500ml or 1 Litre

Application

Apply Surface Activator with a clean cloth. By doing so the surface is cleaned, degreased and activated for the application of a sealant. Replace cloth regularly when dirty. Leave to evaporate for 5 minutes. Apply sealant / adhesive immediately after evaporation. Gloves and goggles should be worn. Observe good industrial hygiene practices.

Special comments

Important Notice

Data contained in this document is for information only and is believed to be reliable. Trade Grade Products Ltd (TGP) cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability of the product for any specific purpose and TGP is pleased to provide a sample upon request.

Before using this product ensure that you have been supplied with and have read carefully the following information.

- The hazard label (complying with latest CDG/CPL regulations) applied to the container.
- Material Safety Data Sheet, TGP Surface Cleaner.