



## K44 Duo Codelock with 30 codes

Access Control

- Programmable codelock for two doors
- Sturdy construction for outdoor and indoor use
- Alarm output
- Up to 20 codes can be used

The K44 Duo is a programmable codelock for one or two doors. It is possible to set separate codes for each door or the same code for both. K44 Duo also provides the option of door control and alarm output. All programming is done via the keypad. The K44 Duo has a code capacity of 20 four-digit codes and 10 six-digit codes. By using the K44 Duo's tamper switch in combination with the SK5 security unit, it is possible to achieve a higher level of security.

## Technical data

---

<b>K44 Duo</b>	
Operating voltage	10 to 35 VDC 8 to 24 VAC
Current consumption	75 mA in standby
Inputs	Two exit button requests with delay. Two separate for codes disable. Two for door contacts. External control of zero opening.
Outputs	Two voltage-free relay contacts, max. 2 A, 28 VDC. Open collector for duress/alert. Open collector for door bell. Tamper switch for alarm connection (normally closed).
Opening time	1-99 seconds programmable from keypad
Door capacity	2
Code capacity	20 four-digit codes and 10 six-digit codes
Operating temperature	-35 to +55 °C
Environment	Indoor or outdoor use (IP54 design). In very exposed locations, use SH2 or SH1 rain cover.
IP rating	IP54
Housing	Cast metal with stainless steel buttons and security lock
Colour	Grey
Dimensions (W x H x D)	80 x 140 x 40 mm

## Details for ordering

---

Type	Part no	Designation	Weight
K44 Duo	S24246-C3553-A1	Codelock with 30 codes	0.75 kg

Issued by  
Siemens Building Technologies  
Fire & Security Products GmbH & Co. oHG  
D-76181 Karlsruhe  
[www.buildingtechnologies.siemens.com](http://www.buildingtechnologies.siemens.com)

© 2009 Copyright by  
Siemens Building Technologies  
Fire & Security Products GmbH & Co. oHG  
Data and design subject to change without notice.  
Supply subject to availability.