



Overview:

Vanderbilt's WSMK smoke alarm seamlessly blends style and security resulting in a class leading product. The smoke alarm compliments the security detection, ensuring the safety of the building occupants. The devices are easy to mount, easy to pair, and easy to configure, ensuring installation time is minimized. In addition, this device uses enhanced, low current RF technology which provides superior communications and ensures long battery life.

Class leading fire protection:

- Autonomous or system based operation
- ✓ CPR EN14604









Superior RF and battery performance:



Long battery life

With high performance Lithium batteries and APS (Automatic Power Save) technology the WSMK detectors have a battery life of 10 years.



Long RF range

500m range in open space means that a single transceiver can cover the majority of installations.

Quick installation and configuration:



Easy to mount

• The WSMK can be mounted and enrolled in minutes. Three screws to fix, push button to enroll and twist to fit into mounting bracket. Operation of the test button will activate the internal sounder and associated SPC panel.



Easy to pair

Smart Pairing mechanism allows the device to pair with the SPC transceiver in seconds.

Key features include:

- Manual pairing button
- Local visual and audible confirmation of pairing



Easy to configure

The WSMK device is entirely firmware configurable 'over the air'. Configurable features include:

- _____
- Supervision time
- LED behaviour











Transmission:

₩A	Frequency Band	868-869MHz			
Battery / Power:					
	Power Supply	WSMK: 2 x 1.5v Lithium batteries, (type: Energizer L91)			
	Battery Life	≥ 10 years			
	Range in open space	Up to 500m in open space			
٢	Current Draw	Standby ~18µA Alarm 200mA			
Å	Transmit power	~ 13dBm			
۵	APS Automatic Power Saving	Yes			





Intrusion Detection Properties:

\diamond	Detection Method	Photoelectric chamber for smoke detection
()	Supervision Time	7 min by default (programmable between 1 to 30 min)
(D	Event Transmission	Alarm, Tamper, Keep Alive, Battery status
0	Audible warning	85dB @ 3m







Mounting specifications:

	Operating Temperature	-10°C to +55°C
\bigcirc	Dimensions	125x125x38mm
Ø	Weight (Inc. battery)	235g
	LED Indications	Bi-colour LED indications for monitoring and pairing



Ordering Information:

Туре	Art. No	Description
WSMK	V54538-F113-A100	Wireless Smoke Alarm





VANDERBILT

vanderbiltindustries.com

♥ @VanderbiltInd

in Vanderbilt Industries

Vanderbilt International Ltd.

Clonshaugh Business and Technology Park Clonshaugh, Dublin D17 KV 84, Ireland

Sec. +353 1 437 2560